CRAFCO® INC
AN ERGON COMPANY
6165 W. Detroit St.
Chandler, AZ 85226
(602) 276-0406 (800) 528-8242
FAX: (480) 940-0313

QUOTE # AAAQ11985-06

Date Quoted 1/12/2018
EXPIRATION DATE 2/28/2018

Quote To: Account Code: $$$Error:002:Conta

Maidencreek Township
Keith Shuman
1 Quarry Road
PO Box 319
Blandon, PA 19510
United States of America
Phone: 610-926-4920
Fax: 610-926-6314
Email: maidentwp@aol.com

Ship To: Account Code: $$$Error:002:Contact r

Maidencreek Township

1 Quarry Road
PO Box 319
Blandon, PA 19510
United States of America

Keith Shuman
610-926-4920 maidentwp@aol.com

Project Title: **General Purchase**

Bid Date:
Bid Number:
Project Start Date:
Ship Before: 2/28/2018
Quote Effective Dates: 8/14/2017 TO 2/28/2018

Terms: NET 30
F.O.B.: ORIGIN/PREPAID/CHARGED BACK
Ship Via: Truck/Common Carrier
Sales Group:
Quoted By: Brian Hatfield
Sales Office: ER7- Brian Hatfield

Estimated Time to Ship After Receipt of Order: Quoted at time of order

Customer: **Maidencreek Township**
Project Title: **General Purchase**

Quote Number AAAQ11985-06
Date 01-12-18

SALES TAX EXEMPT CERTIFICATE MUST BE PROVIDED AT THE TIME OF ORDER OR SALES TAX WILL BE ADDED TO YOUR ORDER

Part #	Description	Unit	Qty.	Quote Price	Ext. Price
34518-3-PA07	POLYFLEX TYPE 2	LB	2,250	$0.3900	$877.5000
34681-05-PA07	DETACK	PL	1	$62.1300	$62.1300

COMMENTS:

REVISION #6-Extended quote duration and amended price
Sealant is sold by the pound in pallet quantities of 2250 lbs
Detack is sold by the 5 gallon pail
For ordering contact Allentown customer service at 610-264-7541
Sales contact: Brian Hatfield 717-678-2961 brian.hatfield@crafco.com
or
Pete Libby 717-312-3164
pete.libby@crafco.com

CRAFCO INC
AN ERGON COMPANY
420 N. Roosevelt Ave. • Chandler AZ 85226
1-800-528-8242 • (602) 276-0406 • FAX (480) 961-0513
www.crafco.com

PRODUCT DATA SHEET

POLYFLEX TYPE 2

PART NO. 34518

JANUARY 2008

READ BEFORE USING THIS PRODUCT

GENERAL

Crafco PolyFlex Type 2 is a hot-applied, asphalt based product used to fill cracks and joints in asphalt or portland cement concrete pavements in moderate to warm climates. PolyFlex Type 2 is supplied in solid form which when melted and properly applied forms a highly adhesive and flexible compound that resists cracking in the winter and resists flow at summer temperatures. PolyFlex Type 2 is used in highway, street, airfield and parking lot pavements and is applied to pavement cracks using pressure feed melter applicators. At application temperature PolyFlex Type 2 is a medium viscosity product which flows and penetrates cracks. PolyFlex Type 2 is formulated as an economical yet effective pavement maintenance crack filling product. Compared to products based on reclaimed rubber, PolyFlex Type 2 offers lower viscosity for easier application, improved summer temperature pick-up resistance, quicker set times, and improved low temperature flexibility. Polyflex Type 2 has been a quality Crafco product for 20 years. Several states have developed specifications based on performance of PolyFlex Type 2. VOC = 0 g/l.

USAGE GUIDELINES

PolyFlex Type 2 pavement temperature performance limits are 64-16 for crack filling. Usage recommendations are shown in Crafco pavement temperature grade charts shown at the right. Refer to Crafco Product Selection Procedures to determine sealant or filler use and pavement temperature grades.





Pavement Temp for Filler Usage

SPECIFICATION CONFORMANCE

The Crafco recommended specification limits for PolyFlex Type 2 when heated in accordance with ASTM D5078 to the maximum heating temperature are as follows:

Test	Specification Limits
Cone Penetration,77°F(25°C)(ASTM D5329)	35-55
Resilience (ASTM D5329)	40% min.
Softening Point (ASTM D36)	200°F (93°C)min
Ductility 77°F(25°C)(ASTM D113)	30cm min
Flexibility (ASTM D3111 Modified)	Pass at 20°F (-7°C)
Flow, 140°F(60°C) (ASTM D5329)	3 mm max.
Brookfield Viscosity, 400°F(204°C) (ASTM D2669)	100 Poise max.
Asphalt Compatibility (ASTM D5329)	Pass
Bitumen Content (ASTM D4)	60% min.
Tensile Adhesion (ASTM D5329)	500% min.
Maximum Heating Temperature	400°F (204°C)
Minimum Application Temperature	380°F (193°C)

INSTALLATION

The unit weight of Crafco PolyFlex Type 2 sealant is 10.0 lbs. per gallon (1.20 kg/L) at 60°F (15.5°C). Prior to use, the user must read and follow. Installation Instructions for Hot-Applied RoadSaver, PolyFlex and Asphalt Rubber Products to verify proper product selection, heating methods, pavement preparation procedures, application geometry, usage precautions and safety procedures. These instructions are provided with each pallet of product.

PACKAGING

Packaging consists of individual boxes of products which are palletized into shipping units. Boxes contain a non-adherent film which permits easy removal of the product. Each pallet contains 72 boxes which are stacked in six layers of 12 boxes per layer. The weight of product in each box does not exceed 40 lbs. (18kg) and pallet weights do not exceed 2,880 lbs. (1310 kg). Pallets of product are weighed and product is sold by the net weight of product. Product boxes are manufactured from double wall kraft board producing a minimum bursting test certification of 350 psi (241 N/cm^2) and using water resistant adhesives. Boxes use tape closure and do not contain any staples. Boxes are labeled with the product name, part number, lot number, specification conformance, application temperatures and safety instructions. Palletized units are protected from the weather using a three mil thick plastic bag, a weather and moisture resistant cap sheet and a minimum of two layers of six month u.v. protected stretch wrap. Pallets are labeled with the product part number, lot number and net weight. Installation Instructions are provided with each pallet in a weather resistant enclosure.

WARRANTY

CRAFCO, Inc. warrants that CRAFCO products meet applicable ASTM, AASHTO, Federal or State specifications at time of shipment. Techniques used for the preparation of the cracks and joints prior to sealing or filling are beyond our control as are the use and application of the products; therefore, Crafco shall not be responsible for improperly applied or misused products. Remedies against Crafco, Inc., as agreed to by Crafco, are limited to replacing nonconforming product or refund (full or partial) of purchase price from Crafco, Inc. All claims for breach of this warranty must be made within three (3) months of the date of use or twelve (12) months from the date of delivery by Crafco, Inc. whichever is earlier. There shall be no other warranties expressed or implied. **For optimum performance, follow Crafco recommendations for product installation.**

©2008, Crafco, Inc., All Rights Reserved